

A Standard Definition for Wind-Generated, Low-Frequency Ambient Noise Source Levels

Presented at the
116th Meeting of the
Acoustical Society of America,
14-18 November 1988, Honolulu, Hawaii

William M. Carey
David Browning
Surface Anti-Submarine Warfare Directorate

William A. Von Winkle
Associate Technical Director for
Research and Technology

Douglas J. Kewley
Maritime Systems Division, DSTO-WSRL
Australia



Naval Underwater Systems Center
Newport, Rhode Island / New London, Connecticut

AD-A205 758

Preface

This report was prepared under NUSC overhead no. 710Y11.

Reviewed and Approved: 9 February 1989

A handwritten signature in dark ink, appearing to read 'W A Von Winkle', is positioned above the printed name.

**W. A. Von Winkle
Associate Technical Director
for Research and Technology**

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT APPROVED FOR PUBLIC RELEASE DISTRIBUTION UNLIMITED		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) NAVAL UNDERWATER SYSTEMS CENTER TD 8481			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION NUSC	6b. OFFICE SYMBOL (if applicable) 302	7a. NAME OF MONITORING ORGANIZATION			
6c. ADDRESS (City, State, and ZIP Code). NEW LONDON LABORATORY NEW LONDON, CT 06320		7b. ADDRESS (City, State, and ZIP Code)			
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO.	PROJECT NO. 710Y11	TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) A STANDARD DEFINITION FOR WIND-GENERATED, LOW-FREQUENCY AMBIENT NOISE SOURCE LEVELS					
12. PERSONAL AUTHOR(S) WILLIAM M. CAREY, WILLIAM A. VONWINKLE, DAVID G. BROWNING AND DOUGLAS J. KEWLEY					
13a. TYPE OF REPORT	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 1989 Feb. 9		15. PAGE COUNT 34	
16. SUPPLEMENTARY NOTATION Presented at the 116th Meeting of the Acoustical Society of America, 14-18 November 1988, Honolulu, Hawaii					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Ambient Noise Prediction Models		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>Low-frequency, wind-generated ambient noise source levels are important input parameters for newly developed ambient noise prediction models such as DUNES. However, there has been a significant variation among recently reported source levels. An analysis is made of these values. Although the actual noise measurements, the assumed source model, and a small angle approximation are similar for all papers; differences arise due to additional geometrical factors or a further approximation to shift the source level to the surface. A standard source level definition and evaluation method are proposed. Standard values of low-frequency, wind-generated source levels are presented based on this strategy.</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL W. M. Carey			22b. TELEPHONE (Include Area Code) (203) 440-6699		22c. OFFICE SYMBOL 302

TABLE OF CONTENTS

	Page
A Standard Definition for Wind-Generated Low Frequency Ambient Noise Source Levels.	1
Wind-Generated Ambient Noise Source Levels	3
Ambient Noise Models and Calculations.	5
Source Level Specification	7
Source Level Conversion Factors.	9
Theoretical Relationships Between Monopole and Dipole Dipole Intensities	11
The Geometry	13
Source Near the Sea Surface.	15
Table of Relative Source Level Values.	17
Source Level Considerations.	19
Recommended Source Level-Convention I.	21
Source Level Convention II	23
Conclusions.	25
Bibliography	27
Appendix A -- Frequency Convention	29
Appendix B -- Derivation of the Farfield Intensity and Acoustic Power Expressions for the Acoustic Dipole.	31

Accession For	
NTIS GOR&I	<input checked="" type="checkbox"/>
NTIS IAP	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



A STANDARD DEFINITION FOR WIND-GENERATED LOW FREQUENCY AMBIENT NOISE SOURCE LEVELS

**WILLIAM M. CAREY, WILLIAM A. VONWINKLE,
DAVID G. BROWNING
NEW LONDON LABORATORY,
NAVAL UNDERWATER SYSTEMS CENTER
NEW LONDON, CT 06320**

**DOUGLAS J. KEWLEY
MARITIME SYSTEMS DIVISION, DSTO-WSRL
SALISBURY, 5108 AUSTRALIA**

WU-11-14-44-00760-13P

Low-frequency, wind-generated ambient noise source levels are important input parameters for newly developed ambient noise prediction models such as DUNES. However, there has been a significant variation among recently reported source levels. An analysis is made of these values. Although the actual noise measurements, the assumed source model, and a small angle approximation are similar for all papers; differences arise due to additional geometrical factors or a further approximation to shift the source level to the surface. A standard source level definition and evaluation method are proposed. Standard values of low-frequency, wind-generated source levels are presented based on this strategy.



WIND-GENERATED AMBIENT NOISE SOURCE LEVELS

THIS PAPER

- PROPOSES A STANDARD DEFINITION AND CONVENTION
- SHOWS A COMPARISON OF MEASUREMENTS
- CONCLUDES THAT NO FUNDAMENTAL DIFFERENCES EXIST

THE PURPOSE IS TO CLARIFY APPARENT CONTRADICTIONS IN
REPORTED AMBIENT NOISE SOURCE LEVELS.

01070 1E

Wind Generated Ambient Noise Source Levels

For several years we have been examining ambient noise data from omnidirectional hydrophones, horizontal arrays and vertical arrays. Northern hemisphere data for the most part clearly shows the dominance of shipping noise in the low frequency(< 200 Hz) region. However, selected Northern Hemisphere data obtained with both omnidirectional hydrophones below critical depth and high resolution vertical arrays, as well as Southern Hemisphere data, indicates a wind driven noise mechanism in this low to mid frequency range. The numerical estimation of the properties of mid-basin ambient noise fields which result from wind driven noise requires a determination of the source level and the directional characteristic. Source level estimates which have been published are based on experimental data; however, the conversion from the measured omnidirectional or beam level data needs to be carefully examined. We have encountered difficulty in the direct comparison of published results because of this required conversions to source level. Furthermore, the specification of source level in computer codes used to calculate these noise fields also requires care due to the multitude of conventions and the characteristics of the particular propagation model being used. In our opinion, a standard definition of source level and characteristics would have been most helpful. The purpose of this paper is to supply a sound rational and standard specification for wind driven noise source level.



CURRENT MODEL ASSUMPTIONS AND APPROXIMATIONS FOR WIND-GENERATED AMBIENT NOISE SOURCE LEVELS

MOST MODELS ASSUME EITHER

- A MONOPOLE OR DIPOLE LAYER
- A LAYER DEPTH(S)
- A SMALL ANGLE APPROXIMATION (DISTANT SOURCE)
- A SHIFT TO SURFACE (DISTANT SOURCES)
- A SOURCE LEVEL BASED ON MEASURED OMNI-DIRECTIONAL NOISE AND A CONVERSION FACTOR

... 01070 3E

Ambient Noise Models and Calculations

Calculations of mid-basin ambient noise levels require the use of a specific propagation code (PE, RAYTRACE, ASTRAL, NORMAL MODE, etc). The specification of noise intensity per unit area with respect to $1/r^2$ does not clearly specify the levels one must use with each type of propagation code. Most computations employ one of the approaches shown on this graph. For example, calculations performed with PE (Carey 1987) require the specification of a monopole source level and the depth of the source beneath the pressure release surface. A Ray Trace Code, on the other hand, may well use a dipole source with a level based on measured omnidirectional noise level. All methods require a source level specification which can be related to measured data.



SOURCE LEVEL DEFINITION

$$\begin{aligned}\text{SOURCE LEVEL (SL)} &\equiv 10 \text{ LOG } \left[\frac{\text{POWER RADIATED AT METER}}{\text{REFERENCE POWER}} \right] \\ &= 10 \text{ LOG } \left[\frac{\text{INTENSITY AT ONE METER}}{\text{REFERENCE INTENSITY}} \right]\end{aligned}$$

SL HAS UNITS dB RE $1\mu\text{Pa}$ @ 1 METER WHEN THE
REFERENCE POWER (WATTS) AND REFERENCE INTENSITY
(WATTS/M²) ARE BASED ON A PRESSURE OF $1\mu\text{Pa}$.

Source Level Specification

This vugraph shows the standard definition of source level. This definition usually applies to a monopole source of sound. The reference power or intensity is commonly based on a plane wave with pressure, $p_R = 1 \text{ MPa}$ and intensity $I_R = p_R^2 / \rho c$. This definition has been applied to a dipole by measuring the intensity on the maximum response axis. The purpose of this paper is to provide a method of source level specification for surface distributed sources of ambient noise.



EXPRESSIONS USED TO CONVERT MEASURED OMNI-DIRECTIONAL NOISE LEVELS (NL_o) TO DIPOLE SOURCE LEVEL (SL_D)

A AMPLIFICATION FACTOR

P PROFILE FACTOR

BURGESS & KEWLEY $SL_D = NL_o - 8 \text{ dB} - A - P$

BANNISTER $SL_D = NL_o - 4.97 \text{ dB}$

WILSON $SL_D = NL_o - 10 \text{ LOG } (\pi) - NL_o - 4.97 \text{ dB}$

KUPERMAN $SL_D = NL_o - 10 \text{ LOG (COMPUTER-}$
GENERATED CONSTANT)

Source Level Conversion Factors

Shown on this vugraph are equations used by several investigations to convert omnidirectional noise levels (N_{ho}) to wind driven source levels (SL_0). Burgess and Kewley convert the local omnidirectional noise level to source level by use of an implication factor (A) resulting from multiple reflections at the bottom and surface (depends on bottom loss),

$$8 = 10 \log (2\pi)$$

which results from integration of the sound intensity over a hemisphere, and a sound velocity profile factor (P) which is a measure of the deviation away from hemisphere isotropy. The units of source level are at 1 meter. We note that an appropriate value for $A \sim 3$ indicates that when $P \sim 1$ the expression used by Burgess and Kewley agrees with Bannister and Wilson. Kuperman assumes a layer of monopoles a distance $z' \ll \lambda/4\pi$. Integration over the whole plane yields a computer generated constant 6.34dB.

Thus there are some differences in these conversion expressions which can result in factors on the order of 1-5dB.



THEORETICAL RELATIONSHIPS BETWEEN MONOPOLE AND DIPOLE INTENSITIES USED BY SEVERAL INVESTIGATORS

KUPERMAN	$10 \text{ LOG } (I_D/I_M) = 21.9 + 20 \text{ LOG } (h/\lambda) - 6.34 \text{ dB}$
TALHAM	$= 10 \text{ LOG } (\pi^2) = 9.94 \text{ dB}$
WILSON	$= 10 \text{ LOG } (\pi^2) = 9.94 \text{ dB}$
BANNISTER	$= 10 \text{ LOG } (4) = 6 \text{ dB}$
BURGESS & KEWLEY	$= 10 \text{ LOG } (\pi^2) = 9.94 \text{ dB}$


01070 SE

Theoretical Relationships Between Monopole and Dipole Intensities

The term dipole refers to two point sources of opposite sign separated by one half wavelength. In the context of this discussion we use dipole loosely to mean the field due to a source and its image in the pressure release surface when the distance beneath the pressure release surface is less than a quarter wavelength. Shown on this vugraph are expressions for the maximum response axis intensity (I_D) compared to the monopole intensity used by each investigator. We observe differences between 3.6-4dB. The reason for these differences will become apparent in the following vugraphs.



THE GEOMETRY



01070 6E

The Geometry

The purpose of the vugraph is to illustrate the geometry considered for a point source a distance h beneath the pressure release surface. The convention being adopted is to take θ as 0 on the surface and $\pi/2$ in the downward direction. $|r_0|$ is the radial distance to the observation point and in the farfield of the source and its image and is approximately equal to the $|r_s|$ and $|r_c|$. The problem will assume a unity surface reflection coefficient and each source acting as a spherical radiator.



SOURCE NEAR SEA SURFACE

DIPOLE PRESSURE: $p_D(r_o) = \frac{2 p_o}{4\pi r_o} \sin(k h \sin \theta)$ (1)

DIPOLE INTENSITY: $I_{D_0} = 4 \cdot I_M \sin^2(k h \sin \theta)$ (2)

$$I_{D_1} = 16\pi^2 I_M (h/\lambda)^2 \sin^2 \theta$$
 (3)

WHEN: $k = 2\pi/\lambda$ AND $h/\lambda = 1/4$ (4)

$$I_{D_2} = \pi^2 I_M \sin^2 \theta$$

DIPOLE POWER RADIATED INTO A HEMISPHERE, ($r_o = 1$ METER):

$$P_{D_0} = 4\pi \cdot I_M \left[1 - \frac{\sin(2k h)}{2k h} \right]$$
 (5)

$$P_{D_1} = 32 \frac{\pi^3}{3} (h/\lambda)^2 I_M$$
 (6)

$$P_{D_2} = (2/3 \pi^3 I_M)$$
 (7)

01070 8E

Source Near the Sea Surface

Shown on this vugraph are the equations governing sound radiation from a point source under a pressure release surface. We are assuming the surface reflection coefficient is equal to unity and that the source is harmonic in time and propagates as an outward going spherical wave. Several approximations can be made concerning expressions for the intensity and power radiated by such a source.

Equation 1 shows the result for the magnitude as a summation of the radiated pressure from the source and its image. The monopole source strength is P_0 and the pressure at r_0 from a monopole is $P_M = P_0 / 4\pi r_0$.

Equation 2 shows the intensity at the radial distance r_0 . The monopole intensity is $I_M = P_M^2 / 2\rho c = P_0^2 / (4\pi)^2 r_0^2 (2\rho c)$. Here we have when $\theta = \pi/2$ that $I_{D0} / I_M = 4$. This is the first expression for the relationship between source levels.

Equation 3 shows the result of a small argument of the sine function, ($h/\lambda < 1$). In this instance we find $I_{D1} / I_M = 16\pi^2 (h/\lambda)^2$ when $\theta = \pi/2$. The dipole source level depends on h/λ .

Equation 4 shows the result when we have a true dipole $h/\lambda = 1/4$. Then the intensity $I_{D2} / I_M = \pi^2$ @ $\theta = \pi/2$. At this point we have three possible expressions for the source levels.

Equation 5, 6, and 7 shows the expressions for the radiated power into a hemisphere. We have chosen a hemisphere as only the lower half plane receives radiated energy.



TABLE OF RELATIVE SOURCE LEVEL VALUES

BASED ON ANALYTICAL EXPRESSIONS FOR THE DIPOLE
INTENSITY AND POWER, WE HAVE:

$$S_D - S_M = 10 \text{ LOG } (I_D/I_M) = 10 \text{ LOG } (P_D/P_M)$$

	'0'	'1'	'2'
$\left(\frac{I_D}{I_M}\right)_{\text{PEAK}}$	4	$16\pi^2(h/\lambda)^2$	π^2
P_D/P_M	$\left[1 - \frac{\text{SIN}(2kh)}{2kh}\right]$	$\frac{8\pi^2}{3}(h/\lambda)^2$	$\frac{\pi^2}{6}^*$

* POWER RADIATED INTO A HEMISPHERE. WHEN THE TOTAL
SPHERICAL RADIATION PATTERN IS CONSIDERED: $P_D/P_M = \pi^2/3$.

01070 9E

Table of Relative Source Level Values

Based on the expressions on the last vugraph we have summarized the various ratios of intensity and power. Here we are using the monopole intensity or power as a reference. Notice there are six possibilities. Our previous vugraph has shown Bannister employed $10\text{Log}(4)=6\text{dB}$, where as Wilson, Talham, and Burgess used $10\text{Log}(\pi^2)=9.94\text{dB}$. All these authors employed the peak or maximum response intensity level.



SOURCE LEVEL CONSIDERATIONS

IF WE LET $h/\lambda = 1/4$ — THE PROBLEM IS SIMPLIFIED

$$\frac{I_D}{I_M} = \pi^2 \sin^2 \theta \quad \underline{SL_D = SL_M + 10 \text{ LOG } (\pi^2 \sin^2 \theta)} \quad (1)$$

WITH THIS DEFINITION, THE SL_D WOULD BE MEASURED
AT $\theta = \pi/2$

$$\bullet \quad SL_D = SL_M + \underbrace{10 \text{ LOG } (\pi^2)}_{9.94 \text{ dB}} \quad h/\lambda = 1/4 \quad \theta = \pi/2 \quad (2)$$

HOWEVER IF WE USE THE RADIATED POWER INTO
THE WATER

$$\underline{SL_{DP} = SL_M + 10 \text{ LOG } (\pi^2/6)} \quad h/\lambda = 1/4 \quad (3)$$

2.16

31070 11E


Source Level Considerations

Carey and Browning have surmised that most physically realizable sources of sound near the surface of the sea have a dipole character. If we are to represent the sources of noise as distribution of dipoles per unit area, then the source depth to wavelength ratio should be equal to $1/4$. This implies a frequency dependent source of sound rather than a monopole at fixed depth and that the source of sound is distributed in depth as well as in area. With this implication, we have expressions for the intensity (equation 2) and power (equation 3). The intensity ratio requires the specification of $\Theta = \pi/2$; the power definition which is based on the total radiated power into the water does not. The specification of the number of independent dipoles per unit area is thus a specification of power radiated per unit area or vice versa. The independence criteria require the spacing between dipole radiated to be greater than the correlation of the hydrodynamic forcing function.



RECOMMENDED SOURCE LEVEL CONVENTION I

FOR THOSE CALCULATIONS EMPLOYING A POINT SOURCE
BELOW THE PRESSURE RELEASE SURFACE



SPECIFY: p_o , h/λ

USE MONOPOLE SOURCE LEVEL $SL_o = 10 \text{ LOG } (p_o^2/p_R^2)$

p_R = REFERENCE PRESSURE, $1 \mu\text{Pa}$

01070 12E

Recommended Source Level-Convention I

Based on our previous discussions we now summarize and recommend a standard convention. For those calculations which require a point source below a pressure release surface we recommend the specification of P_0 and h/λ . The monopole source level is specified with respect to $1 \mu P_2 @ 1 m$. The source level $SL_0 = 20 \log (P_0/P_2)$ has units $dB / ((1 \mu P_2)^2 / m^2 - H_3)$. The m^2 specifies the per unit area dependence of ambient noise.



SOURCE LEVEL CONVENTION II

FOR THOSE CALCULATIONS AND APPLICATIONS WHICH
REQUIRE A DIPOLE IN THE PRESSURE RELEASE SURFACE

DIPOLE  SPECIFY: $h/\lambda = 1/4$

$$I_D \cong \pi^2 I_M \sin^2(\theta) \quad (1)$$

$$P_D = \frac{\pi^2}{6} P_M, \text{ FOR RADIATION INTO THE WATER} \quad (2)$$

BASED ON THE POWER RADIATED

$$SL_D = SL_o + 2.16 \text{ dB} \quad (3)$$

Source Level Convention II

When the calculation requires a surface distribution of dipole sources (in this instance $h/\lambda = 1/4$), the power radiated into the water is given equation 2. This results in a dipole level (equation 3) 2.16 dB greater than the monopole source level. The reference units for dipole sources per unit area are $dB/(14Pa)^2/m^2 - Hz$ at 1 meter. The specification of the source level in terms of total power radiated into the water provided a basis for comparison with omnidirectional measurements and alleviates the problem of maximum response axis intensity levels.



CONCLUSIONS WIND-GENERATED AMBIENT NOISE SOURCE LEVELS

- A STANDARD DEFINITION AND CONVENTION PROPOSED
- THIS STANDARD AT MINIMUM ALLOWS FOR COMPARISON OF MEASUREMENTS
- IN LIGHT OF THIS STANDARD THERE APPEAR TO BE NO FUNDAMENTAL DIFFERENCES

01070 13E

Conclusions

We have concluded that source leads for ambient noise which are distributed over 1 meter should be based on a monopole of strength P_0 a distance $h/\lambda = 1/4$ beneath the pressure release surface:

- Monopole

$$SL_0 = 20 \log(P_0/P_R) \quad \text{dB} // ((14P_R)^2/m^2 - Hz) .$$

$$P_M = 4\pi I_M = P_0^2 / 2\rho c .$$

- Dipole

$$P_D = (\pi^2/6) P_M , \quad \text{power radiated into the water .}$$

$$SL_D = SL_0 + 2.16 \text{ dB} \quad \text{dB} // ((14P_R)^2/m^2 - Hz)$$

We conclude that this allows for comparison with measurements that estimate power radiated per unit area. Furthermore when we apply this standard to measurements previously disclosed, no fundamental differences are observed.

Bibliography

Bannister, R. W., A. S. Burgess, and D. J. Kewley, "Estimation of Source Characteristics From Underwater Noise Field Measurements."

Burgess, A. S., and D. J. Kewley, "Wind-Generated Surface Noise Levels in Deep Water East of Australia," Journal of the Acoustical Society of America, vol. 73, 1983, pp. 201-210.

Carey, W. M., and D. G. Browning, "Low Frequency Ocean Ambient Noise: Measurement and Theory," Sea Surface Sound, B. R. Kerman (ed.), Kluwer Academic Pub., 1987, pp. 361-376.

Ferla, M. C., and W. A. Kuperman, "Wind-Generated Noise in Shallow Water," SACLANTCEN Report SR-70, April 1984.

Kuperman, W. A., and F. Ingenito, "Spatial Correlation of Surface Generated Noise in a Stratified Ocean," Journal of the Acoustical Society of America, vol. 67, no. 6, 1980, pp. 1988-1996.

Talman, R. J., "Ambient-Sea-noise Model," Journal of the Acoustical Society of America, vol. 36, no. 8, 1964, pp. 1541-1544.

Wilson, J. H., "Wind-Generated Noise Modeling," Journal of the Acoustical Society of America, vol. 73, 1983, pp. 211-216.

APPENDIX A: FREQUENCY CONVENTION

RANGE	FREQUENCY	DESIGNATION	DESCRIPTION
SEISMIC	0.02 TO 0.2		
	0.2 TO 2	ULF	ULTRA LOW FREQUENCY
INFRASONIC	2 TO 20	VLF	VERY LOW FREQUENCY
	20 TO 200	LF (LOW)	LOW FREQUENCY
	200 TO 2000	MF (MID)	MID-FREQUENCY
SONIC	2000 TO 20,000	HF (HIGH)	HIGH FREQUENCY
	20,000 TO 200K	VHF	VERY HIGH FREQUENCY
ULTRASONIC	200K TO 2M	UHF	ULTRA HIGH FREQUENCY

APPENDIX B: Derivation of the Farfield Intensity and Acoustic Power Expressions for the Acoustic Dipole

The Wave Equation with Constants

We assume a source of sound which is "point" like at $\mathbf{x}_0 = \mathbf{x}_0(x_0, y_0, z_0)$ emitting waves with a time dependence $e^{i\omega t}$, ($\omega = 2\pi f$).

1.) $\nabla^2 \Psi - (1/c(x)^2) \partial^2 \Psi / \partial t^2 = K \cdot S \cdot e^{i\omega t} \delta(\mathbf{x} - \mathbf{x}_0)$, where $c(x)$ is the sonic speed. $\delta(\mathbf{x} - \mathbf{x}_0)$ is the delta function, and K is constant describing the source strength.

2.) $\Psi \equiv$ VELOCITY POTENTIAL $= \Phi(x, y, z) e^{-i\omega t}$; $\mathbf{v} = -\nabla \Psi$; $\rho = \rho \partial \Psi / \partial t$.

3.) $\nabla^2 \Phi + (\omega^2/c^2) \Phi = K \cdot S \cdot \delta(\mathbf{x} - \mathbf{x}_0)$. We need to determine the wave function and the constant K for a wave diverging omnidirectionally from the unit source. In the immediate vicinity of the source, the wave diverges spherically.

4.) $\Phi = (1/R) e^{i\omega R/c}$, $\omega R/c \ll 1$; $R = |\mathbf{x} - \mathbf{x}_0|$.

To find K we integrate over a small sphere of volume V_ϵ with radius ϵ about \mathbf{x}_0 . Then we take the limit as $\epsilon \rightarrow 0$ and let $S=1$.

5.) $\iiint_{V_\epsilon} dV_\epsilon (\nabla^2 \Phi + (\omega^2/c^2) \Phi) = \iiint_{V_\epsilon} dV_\epsilon (K S \delta(\mathbf{x} - \mathbf{x}_0))$.

6.) It is easily shown that $\iiint_{V_\epsilon} dV_\epsilon (\nabla^2 \Phi) = -4\pi$; $\iiint_{V_\epsilon} dV_\epsilon (\omega^2/c^2 \Phi) = 0$.

7.) $\iiint_{V_\epsilon} dV_\epsilon \cdot K \cdot S \delta(\mathbf{x} - \mathbf{x}_0) = -4\pi = K$ by virtue of the delta function.

8.) $\nabla^2 \Phi + (\omega^2/c^2) \Phi = -4\pi \delta(\mathbf{x} - \mathbf{x}_0)$; $\Phi = e^{\pm i\omega R/c} / R$.

9.) Cylindrical coordinates, $(1/r) \partial/\partial r (r \partial \Phi / \partial r) + \partial^2 \Phi / \partial r^2 + \omega^2/c^2 \Phi = -4\pi \delta(r) \delta(z - z_0) \delta(\phi)$.

10.) After integration over ϕ , $(1/r) \partial/\partial r (r \partial \Phi / \partial r) + \partial^2 \Phi / \partial r^2 + \omega^2/c^2 \Phi = -2\pi \delta(r) \delta(z - z_0)$.

The Acoustic Dipole The wave equation in spherical coordinates from equation 1.

11.) $\nabla^2 \Psi + k^2 \Psi = -4\pi q_0 e^{-i\omega t} \delta(\mathbf{r} - \mathbf{r}_0)$. ^(a)

12.) The outward propagating wave $\Psi = (g_0/r) \exp(i\mathbf{k} \cdot \mathbf{r} - i\omega t)$.^(b)

where g_0 represents the magnitude of the volume source. The acoustic pressure $P = \rho \partial \Psi / \partial t$ and the particle velocity $\underline{V} = -\nabla \Psi$.

The solution to the wave equation at point r_0 from a point source at r_s and its image at r_i is the superposition of individual solutions. In this instance the source is a distance h beneath the pressure release surface.

13.) $\Psi(r_0) = \Psi_s(r_s) + \Psi_i(r_i)$; $P(r_0) = P_s(r_s) + P_i(r_i)$; $|r_s| \approx |r_i| \approx |r_0|$; $M = -1$.

$$r_s^2 = x^2 + (y-h)^2; \quad r_i^2 = x^2 + (y+h)^2; \quad r_0^2 = x^2 + y^2.$$

$$\Psi(r_0) = (g_0/r_0) \exp(i\mathbf{k} \cdot \mathbf{r}_0 - i\omega t) [\exp(-i\mathbf{k} \cdot \mathbf{r}_0 h / r_0) - \exp(+i\mathbf{k} \cdot \mathbf{r}_0 h / r_0)].$$

The resulting velocity potential function is

$$14.) \Psi(r_0) = (g_0/r_0) \exp(i\mathbf{k} \cdot \mathbf{r}_0 - i\omega t) (-2i) \sin(kh \sin \theta).$$

The pressure is determined by use of $P = \rho \partial \Psi / \partial t$.

$$15.) P(r_0) = (-2\rho g_0 \omega / r_0) \sin(kh \sin \theta) \exp(i\mathbf{k} \cdot \mathbf{r}_0 - i\omega t); \quad |P(r_0)| = \frac{2\rho g_0 \omega}{r_0} \sin(kh \sin \theta).$$

The acoustic intensity is by definition,

$$16.) I_D = \text{Re}(u^* P) = (4R\omega\rho g_0^2 / r_0^2) \sin^2(kh \sin \theta) = (4\omega^2\rho g_0^2 / c r_0^2) \sin^2(kh \sin \theta).$$

where D refers to the source and its image.

17.) The point source, monopole, intensity is $I_M = \omega^2\rho g_0^2 / r_0^2 c$. The radiated intensity from the source and image.

18.) $I_D = 4I_M \sin^2(kh \sin \theta)$. The radiated power into the lower hemisphere.

$$19.) P_D = \int I_D dA = \int_0^{2\pi} d\phi \int_0^{\pi/2} d\theta r_0^2 (4\omega^2\rho g_0^2 / r_0^2 c) \sin^2(kh \sin \theta) \cos \theta.$$

$$20.) P_D = (4\pi\omega^2\rho g_0^2 / c) [1 - \sin(2kh) / 2kh]. \quad P_M = 4\pi\omega^2\rho g_0^2 / c.$$

The result of the derivation is the following expression for intensity and power.

21.) The general result.

$$a.) I_M = \omega^2\rho g_0^2 / c$$

$$b.) I_D = 4I_M \sin^2(kh \sin \theta)$$

$$c.) P_M = 4\pi I_M$$

$$d.) P_D = 4\pi I_M [1 - \sin(2kh) / 2kh]$$

$$e.) I_D / I_M = 4 \sin^2(kh \sin \theta)$$

$$f.) P_D / P_M = (1 - \sin(2kh) / 2kh)$$

22.) The approximation $kh \ll 1$ $kh = 2\pi h/\lambda$

$$a.) I_D = 16\pi^2 (h/\lambda)^2 \sin^2 \theta I_M \quad I_D/I_M = 16\pi^2 (h/\lambda)^2 \sin^2(\theta)$$

$$b.) P_D = (32\pi^3/3) (h/\lambda)^2 I_M \quad P_D/P_M = (8\pi^2/3) (h/\lambda)^2$$

23.) The approximation $2\pi h/\lambda = \pi/2$

$$a. I_D/I_M = \pi^2 \sin^2 \theta \quad b.) P_D/P_M = \pi^2/6$$

Note: (a) When the radiation from a point source is taken of the form $1/r \exp(-i\omega t + i\mathbf{k} \cdot \mathbf{r})$, the solution will be Hankel functions of the first kind (i.e., Morse) when the solution is of the form $1/r \exp(i\omega t - i\mathbf{k} \cdot \mathbf{r})$ we must use Hankel function of the second kind.

Note: (b) We have a choice $e^{i\mathbf{k} \cdot \mathbf{r}}/r$ or $e^{i\mathbf{k} \cdot \mathbf{r}}/4\pi r$, we have chosen the first form.

INITIAL DISTRIBUTION LIST

Addressee	No. of Copies
CNO	3
DTIC	2
DTIC/NAVAL TECHNOLOGY OFFICE (R. Clark, C. Stuart, K. Hawker)	3
DARPA	5
CNO (OP-091, -952, NOP-096)	3
CNR (OCNR-00, -10, -11, -1125 (Marshall Orr, R. Robractal), -13 (K. W. Lackie, K. Dial, E. Chaika), -20, ONT-23, -234, -230)	12
ONR DET BAY ST. LOUIS	2
NAVAIRSYSCOM (NAIR-93, -933)	2
SPACE & NAV WARFARE SYS CMD (PMW-180 (R. Doolittle, J. Synsky, CAPT K. Evans, CAPT R. Witter))	4
NAVSEASYS COM (SEA-63)	1
NRL (NRL 5100, 5120, 5160, 5130 (N. Yen))	5
NORDA (245 (R. Wagstaff), 110 (W. Moseley), 200 (E. Franchie), 240 (R. Farwell), 125L (Library))	5
NEPRF	1
NADC	1
NCSC	1
NOSC	1
DTRC CADEROCK LAB	2
NSWC WHITE OAK LAB	2
NPS (Dr. H. Medwin)	5
NUSC DET AUTEC	1
NUSC DET WEST PALM BEACH (R. Kennedy)	1
APL/JOHNS HOPKINS (G. Smith)	1
APL/U. WASHINGTON (R. Spindel)	2
ARL/PENN STATE (S. McDaniels, D. McGammon)	3
ARL/U. TEXAS (S. Mitchell)	3
MPL/SCRIPPS (F. Fisher, W. Hodgkiss)	3
WOODS HOLE OCEAN. INSTI. (S. Williams, G. Frisk, J. Lynch)	5
U. OF MIAMI (F. Tappert, H. DeFarrari)	2
BOLT BERANEK & NEWMAN, INC. (P. Cable, S. Marshall, W. Marshall, G. Duckworth, P. Smith)	5
SAI CORP., McLean, VA (A. Eller)	3
SAI CORP., New London, CT (F. DiNapoli)	3
SYNTEC (R. Evans)	1
TRW (S. Gerben)	1
MIT (H. Schmidt, A. Baggeroer, I. Dryer)	3
U. OF DELAWARE (V. Klemas, P. Lyrenga, D. Wood)	3
SEA GRANT OFFICE, AVERY POINT (E. Monahan)	1
LaJOLLA INSTITUTE	1
DEFENCE SCIENTIFIC ESTABLISHMENT (Dr. Richard Bannister)	1
DEFENCE RES. EST. PACIFIC (Dr. Robert Chapman, Dr. R. Chapman)	2
DEFENCE RES. EST. ATLANTIC (Dr. Harold Merklinger)	1
UNIVERSITY OF AUCKLAND (Dr. Alick Kibblewhite, Dr. Gary Bold)	2
R.A.N. RESEARCH LAB. (Dr. Douglas Cato)	1
ADMIRALTY RES. EST. (Dr. David Weston)	1